


Let us  
entertain  
you



The IW 408 FG is equipped with a rotating, pivoting tweeter and **WaveGuide**. As with most in-wall speakers in the 400 and 600 Custom series, they are designed with special attention to freedom of placement. Due to Jamo's clever **SoundAngle** technology, the speaker can be mounted at a height of several meters, without compromising the sound quality.

Simply set the switch to -30 degrees and the sound will be optimised downwards, aiming at the listening position. If the speaker is installed at normal height, the switch is simply set to 0 degrees.

For more information visit [www.jamo.com](http://www.jamo.com)

**Specifications**

System	<b>IW 408 FG</b> 2-way in-wall
Woofer (mm / in)	203 / 8
Midrange (mm / in)	-
Tweeter (mm / in)	25 / 1 DTT
Power (W long / short term)	80 / 160
Frequency Range (Hz)	55 - 22,000
Impedance (Ohm)	4 - 8 switchable
Hole dimension HxWxD (mm / in)	344 x 240 x 95 / 13.5 x 9.4 x 3.7
Dimensions HxWxD (mm / in)	375 x 270 x 105 / 14.8 x 10.6 x 4.11
Back box size (Litre/in3)	22 / 1340
Weight (kg / lb)	2.2 / 4.9
Finish	White (paintable)



*Soundwise, IW 408 FG is comparable with C 403, C 401, C 400 SUR*

**Jamo**<sup>®</sup>  
Danish Sound Design