ATM 50 Jamo

DOLBY ATMOS® ELEVATION MODULE



SPECIFICATIONS

| FREQUENCY RESPONSE | Conforms to Dolby Atmos Specification |
|-----------------------|--|
| SENSITIVITY | Conforms to Dolby Atmos Specification |
| POWER HANDLING | 50W RMS / 200W Peak |
| NOMINAL IMPEDANCE | 8 Ohm |
| HIGH FREQUENCY DRIVER | 25mm (1") Soft Dome Tweeter |
| LOW FREQUENCY DRIVER | 133mm (5.25") Aluminized Polyfiber Woofer |
| ENCLOSURE MATERIAL | MDF |
| ENCLOSURE TYPE | Sealed MDF Cabinet |
| INPUTS | Single Binding Posts |
| FINISH | Matte Black Polymer Veneer |
| DIMENSIONS | 221mm H, 165mm W, 273mm D 8.70" H, 6.5" W, 10.25" D |
| WEIGHT | 3.5kg (7.8 lbs) |

DOLBY ATMOS EFFECTS

Add Dolby Atmos® height effects to any existing home theater with Jamo ATM 50 on top of your floorstanding or bookshelf speakers for dynamic, 3-dimensional sound for your music and movies.

HIGH PERFORMANCE ACOUSTICS

Coaxial design utilizes point source for focused, immersive elevation effects, while the 1" soft dome tweeter and 5.25" alumized polyfiber woofer provide dynamic, balanced, distortion-free sound.

MATTE POLYMER FINISH

Designer aesthetic that blends with any high performance home theater system.

STRONG, FLEXIBLE GRILLE

Exclusive design provides built-in front stage occlusion for life-like, powerful overhead effects.