

JAMO STUDIO SERIES • S 526 HCS 3



Design

The Jamo S 526 Home Cinema System proves you don't have to compromise either high-quality true surround sound or excellent design if you have a smaller budget to work with. This powerful, 750-watt capable system starts with two S 526 floorstanding speakers with dual woofers for deep bass and compliments them with a perfect match in an S 52 CEN center channel speaker. The compact S 522 speakers provide the enveloping surround sound that puts you in the middle

of everything! Add an optional Jamo SUB 210 subwoofer for the deepest movie bass effects you can feel. Either way, you have a perfect system for movies, TV or music listening. Available in black ash or dark apple finishes, all speakers are neatly complemented by soft-feel black baffles giving the system a premium and contemporary appearance. The S 526 includes optional speaker spikes while the S 522 and the S 52 CEN have built-in keyhole mounts for on-wall applications.

Technology

- 1-inch (25 cm) soft dome tweeters/6.5-inch (16.6cm) or 4-inch(10.2cm) aluminized woofers.
- Bass-reflex design with flared, rear-firing ports: Increases system efficiency and bass output.
- Waveguide: A unique tweeter faceplate that provides more uniform dispersion in the critical frequency range of 2-10 kHz. Dynamics and clarity are enhanced while distortion is significantly reduced.
- Centre-plug: Replaces the typical dust cap and eliminates cone breakup, for a woofer with faster "attack" and tighter, more natural bass.
- Aluminized woofers: Increases cone rigidity for solid bass.
- Individually chambered woofers (S 526): Separately housed woofers minimize driver interference.
- 5-way binding posts: Allows for multiple connection options with wire up to 12 gauge (AWG).

Specifications

	S 526	S 522	S 52 CEN
System Type	2 Way Bass Reflex	2 Way Bass Reflex	2 Way Bass Reflex
Tweeter (mm/in)	25 / 1	25 / 1	25 / 1
Woofer (mm/in)	Dual 165 / 6.5	102 / 4	Dual 102 / 4
Frequency Response (Hz +/- 3 dB)	45-20,000	80-20,000	75-20,000
Power Handling (Watts Long/Short Term)	130 / 180	80 / 130	100 / 140
Sensitivity (dB, 2.8V/1m)	89	86	87
Crossover Frequency (Hz)	2500	2500	2500
Impedance (Ohm)	6	6	6
Product Dimensions (mm/in, HxWxD)	1000 x 195 x 301 / 39.4 x 7.7 x 11.9	240 x 134 x 202 / 9.4 x 5.3 x 7.9	134 x 400 x 207 / 5.3 x 15.7 x 8.1
Weight (Kg/lb)	15.2 / 33.5	2.7 / 5.9	4.7 / 10.4
Finishes	Black Ash Dark Apple	Black Ash Dark Apple	Black Ash Dark Apple