

Let us entertain you



Normally the installation of THX sound systems require a dedicated room, i.e a home movie theater. The size and the industrial design of virtually all THX systems dictate that the speakers are hidden behind curtains and walls.

Not anymore! The size of the new D 500 THX Select2 loudspeaker system allows direct placement in most medium sized living rooms. In addition to the compact dimensions these speakers are styled in a way that accommodates many contemporary decorations and furniture combinations. Finished in high gloss lacquer these speakers add a musical instrument touch to the modern home.

Equipped with carefully engineered loudspeaker drive units the new D 500 series deliver impeccable reproduction of even the most demanding movie sound track, from the deepest bass to the highest highs. In addition to outstanding movie entertainment the D 500 will give the end user a very satisfying reproduction of music, be it from stereo MP3 files or full scale DVD-Audio or SACD.

Specifications	D 600 SUB	Specifications	D 500 LCR	D 500 SUR
System	Active DSP based subwoofer, sealed enclosure. Motional feedback	System	3-Way Closed	3-Way Closed Dipole
Usef interface	Touch panel with backlight	Woofer (mm / in)	2 x 140 / 5½	1 x 140 / 5½
Woofer (mm / in)	380 / 15	Midrange (mm / in)	2 x 76 / 3	2 x 76 / 3
Rated power (Wrms)	600 @4ΩTHD+N <1%	Tweeter (mm / in)	1 x 25 / 1	2 x 25 / 1
Dynamic power (Wrms)	800 @4Ω	Power (W, long / short term)	150 / 200	120 / 170
Peak power (Wpk)	1600 @4Ω	Sensitivity (dB/2,8V/1m)	89	84
Maximum SPL (dB)	109	Frequency Range (Hz)	80 - 20.000	80 - 20.000
Frequency range (Hz)	20 - 200	Cross-over Frequency (Hz)	400 / 2500	250 / 2500
Variable cut off (Hz)	40 - 200	Impedance (Ohm)	4	8
Phase (deg.)	0 to -180	Weight (Kg / lb)	7,2 / 15.8	6,7 / 14.8
BGC	Variable	Dimension HxWxD (mm / in)	260 x 450 x 130 / 10.2 x 17.7 x 5.1	260 x 450 x 130 / 10.2 x 17.7 x 5.1
Line input	Yes, stereo pass through for daisy chain	Finishes	High Gloss Black or High Gloss White	High Gloss Black or High Gloss White
LFE input	Yes, pass through for daisy chain			
Speaker level input	Yes			
Sensitivity (mVrms)	100			
Sound modes	Default. Personal. THX			
12V trigger	Yes, pass through for daisy chain.			
Mains switch	On / Off			
Voltage switch (fuse)	115V/60Hz (6.3A) / 230V/50Hz (3.15 A)			
Auto enable switch	Off / Auto / On			
Dimension (mm / in)	557 x 587 x 501 / 21.9 x 23.1 x 19.7			
Weight (kg / lb)	32 / 70.5			
Finish	Stone Grey			

One D 600 SUB will meet THX Select2 output levels. THX and theTHX logo are trademarks of THX Ltd. which may be registered in some jurisdictions. All rights reserved.

